Kleene Modules for Routing Procedures

Peter Höfner

NICTA
Sydney, Australia
Computer Science and Engineering
University of New South Wales
Sydney, Australia

In the past, algebraic techniques based on semirings have been used describe shortest path algorithms and routing procedures, e.g. [2, 1, 8, 3, 5]. These approaches often use matrices over semirings/Kleene algebra, which form again a semiring/Kleene algebra.

While these approaches work well for shortest paths algorithms, they fail when modelling timing aspects of routing algorithms. A major shortcoming is that at least one distributivity law has to be dropped on the level of semiring. This implies the loss of associativity on the matrix-level.

In this talk I will present the shortcoming with the help of the Ad hoc On-Demand Distance Vector (AODV) routing protocol [7]. AODV is a widely used and standardised routing protocol designed for wireless mesh networks (WMNs); AODV also forms the basis of new WMN routing protocols, such as the upcoming IEEE 802.11s wireless mesh network standard [4].

I will argue that Kleene module, as defined in [6], can help in this regard. I will show how crucial aspects of routing protocols in general, and AODV in particular, can be modelled using modules. The talk will be concluded with some discussion on on-going developments and future work.

(Joint work with Annabelle McIver)

- [1] R. Backhouse & B. Carré (1975): Regular Algebra Applied to Path-Finding Problems. Journal of the Institute of Mathematics and Applications .
- [2] B. Carré (1980): *Graphs and Networks*. Oxford Applied Mathematics & Computing Science Series, Oxford University Press.
- [3] T. Griffin & J. Sobrinho (2005): Metarouting. SIGCOMM Comp. Com.. Rev. 35, pp. 1–12.
- [4] G. R. Hiertz, D. Denteneer, S. Max, R. Taori, J. Cardona, L. Berlemann & B. Walke (2010): *IEEE 802.11s:* the WLAN mesh standard. *IEEE Wireless Communications* 17(1), pp. 104–111.
- [5] P. Höfner & A. McIver (2011): *Towards an Algebra of Routing Tables*. In H. de Swart, editor: *Relations and Kleene Algebra in Computer Science*. *Lecture Notes in Computer Science* 6663, Springer, pp. 212–229.
- [6] Hans Leiß (2006): Kleene modules and linear languages. J. Log. Algebr. Program. 66(2), pp. 185–194. Available at http://dx.doi.org/10.1016/j.jlap.2005.04.004.
- [7] C. Perkins, E. Belding-Royer & S. Das (2003): Ad hoc On-Demand Distance Vector (AODV) Routing. RFC 3561 (Experimental). Available at http://www.ietf.org/rfc/rfc3561.txt.
- [8] J. Sobrinho (2002): Algebra and algorithms for QoS path computation and hop-by-hop routing in the internet. *IEEE/ACM Trans. Networking* 10(4), pp. 541–550.